

Package: DNLC (via r-universe)

September 17, 2024

Type Package

Title Differential Network Local Consistency Analysis

Version 1.0.0

Date 2016-11-23

Maintainer Yusheng Ding <yushengding93@gmail.com>

Description Using Local Moran's I for detection of differential network local consistency.

License GPL (>= 2)

Imports igraph, spdep, fdrtool, GOstats, locfdr, mvtnorm, caTools

LazyData true

Depends R (>= 2.10)

NeedsCompilation no

Author Yao Lu [aut], Yusheng Ding [aut, cre], Linqing Liu [aut],
Tianwei Yu [aut]

Date/Publication 2016-12-11 12:26:26

Repository <https://yushengding.r-universe.dev>

RemoteUrl <https://github.com/cran/DNLC>

RemoteRef HEAD

RemoteSha a471544877fe1bdfcba0d42b15598b9c02b44cff

Contents

cal_lmi_data	2
DNLC_statistics	3
gene_fdrtest	4
init_simulation_gene_net	4
significant_genes	5

Index

7

cal_lmi_data	<i>Calculate local moran's I matrix for a network and a gene expression matrix</i>
--------------	--

Description

cal_lmi_data() will calculate the local moran's I data for a input igraph object and gene expression data matrix.

Usage

```
cal_lmi_data(gene_expr, gene_graph)
```

Arguments

- | | |
|------------|--|
| gene_expr | Expression for genes. Each row is a gene, and each column is a sample. |
| gene_graph | The graph of gene network. |

Details

cal_lmi_data() will calculate the local moran's I matrix for a input igraph object and gene expression data matrix. The function will return a matrix in the same dimension of the input gene expression matrix. Every gene x's lmi data takes a row.

Value

A table of local moran's I data. Row name is gene id. Each row stands for the local moran's I data of gene x. Each column stands for a sample.

Examples

```
## Not run:
simulation <- init_simulation_gene_net()
lmi_data = cal_lmi_data( simulation$gene_expr, simulation$gene_graph)
t_data = DNLC_statistics(simulation$gene_graph, simulation$gene_expr,
  simulation$patient_matrix, lmi_data = lmi_data)
fdr_result <- gene_fdrtest(t_data)
sig_genes <- significant_genes(fdr_obj = fdr_result, thres = 0.2)
## End(Not run)
```

<code>DNLC_statistics</code>	<i>calculate t statistics for gene graph using DNLC method.</i>
------------------------------	---

Description

a function to calculate t statistics for genes in the graph.

Usage

```
DNLC_statistics(gene_graph, gene_expr = "x", clinic_data = "y",
confounder_matrix = NULL, lmi_data = NULL)
```

Arguments

gene_graph	graph of gene
gene_expr	expr of gene
clinic_data	patient data
confounder_matrix	other message describe clinic message
lmi_data	lmi data for each gene.

Details

This function first calculates the matrix of local moran's I, and then conducts testing for the association of each gene's local moran's I with the clinical outcome variable. Clinical confounder variables such as age, gender etc can be included.

Value

all_gene_id	gene ids in graph
t_data	t-data for each gene

Examples

```
## Not run:
simulation <- init_simulation_gene_net()
t_data = DNLC_statistics(simulation$gene_graph, simulation$gene_expr,
simulation$patient_matrix, lmi_data = simulation$lmi_matrix)
fdr_result <- gene_fdrtest(t_data)
sig_genes <- significant_genes(fdr_obj = fdr_result, thres = 0.2)

## End(Not run)
```

gene_fdrtest	<i>Use local false discovery rate for the detection of genes with significant LMI change</i>
--------------	--

Description

This function use locfdr function to calculate fdr_result

Usage

```
gene_fdrtest(gene.data)
```

Arguments

gene.data	gene_id_all: gene id	t_data: t statistic for each gene
-----------	----------------------	-----------------------------------

Value

return fdr_result for t_data	
fdr\$name	all gene id
fdr\$fdr	fdr value for gene

Examples

```
## Not run:
simulation <- init_simulation_gene_net()
t_data = DNLC_statistics(simulation$gene_graph, simulation$gene_expr,
                         simulation$patient_matrix, lmi_data=simulation$lmi_matrix)
fdr_result <- gene_fdrtest(t_data)
sig_genes <- significant_genes(fdr_obj = fdr_result, thres = 0.2)

## End(Not run)
```

init_simulation_gene_net

Create a random network for simulation

Description

This function will create a network for DNLC. This function will change correlation of chosen genes and its one hop neighbor between treatment groups to simulate LMI changes.

Usage

```
init_simulation_gene_net(base_correlation = 0.4,
                         change_correlation = 0.8, sample_size = 100, num_gene = 5000, change_gene_num=5)
```

Arguments

base_correlation	base correlation of network
change_correlation	change correlation for selected genes
sample_size	multi size of patient data
num_gene	gene number in the network
change_gene_num	number of genes around which the correlation structure is to be changed

Value

lmi_matrix	matrix of local moran's I data
patient_matrix	matrix of patient data
neigh_list	id of changed gene.
gene_graph	igraph object of gene network
gene_expr	gene expression data matirx

Examples

```
## Not run:
simulation <- init_simulation_gene_net()
t_data = DNLC_statistics(simulation$gene_graph, simulation$gene_expr,
                         simulation$patient_matrix, lmi_data = simulation$lmi_matrix)
fdr_result <- gene_fdrtest(t_data)
sig_genes <- significant_genes(fdr_obj = fdr_result, thres = 0.2)
## End(Not run)
```

significant_genes *Selecting significant genes according to fdr result*

Description

Choose the significant genes according to fdr result

Usage

```
significant_genes(fdr_obj, thres)
```

Arguments

fdr_obj	fdr result come from function gene_fdrtest
thres	threshold to identify significant genes

Value

ID of significant genes

Examples

```
## Not run:  
simulation <- init_simulation_gene_net()  
t_data = DNLC_statistics(simulation$gene_graph, simulation$gene_expr,  
    simulation$patient_matrix, lmi_data = simulation$lmi_matrix)  
fdr_result <- gene_fdrtest(t_data)  
sig_genes <- significant_genes(fdr_obj = fdr_result, thres = 0.2)  
  
## End(Not run)
```

Index

cal_lmi_data, 2
DNLC_statistics, 3
gene_fdrtest, 4
init_simulation_gene_net, 4
significant_genes, 5